

- Robust design for arduous in-cab applications
- Return-to-center
- Optional mechanical over-press feature at either ends of travel
- Low under-panel depth of 21mm
- Hall-effect sensor technology
- Rated for 1 million cycles of life
- Dual-redundant electronic architecture
- Outputs with sense and voltage span options
- Dual supply to ensure a high level of signal integrity
- Designed to allow contamination (liquid or dust) to pass through the mechanism without causing any damage
- Electronics sealed to IP67



The JC040 is a proportional rocker for use in joystick grips and other in-cab human-machine interfaces. Two robust, return-to-center operating options are available: a  $\pm 25^\circ$  movement from center; or a  $\pm 20^\circ$  movement with an over-press feature, which can be included in both directions of movement or just one, used to indicate a different mode of machine operation. In all versions, a compact mechanical design means the required under-panel space is just 21mm.

The rocker utilizes non-contacting, Hall-effect sensing technology that eliminates contact wear and provides for long-life integrity of the output signal, giving rise to a minimum operating life of 1 million cycles.

Safety is enhanced via a fully dual-redundant electronic architecture made up of two power supplies and two sensing circuits, the outputs of which can be set to positive or negative ramps or a combination of both. Electronic robustness is assured with the enclosure sealing rated to IP67.



## SPECIFICATIONS

### ELECTRICAL

SUPPLY VOLTAGE	5Vdc $\pm$ 0.5Vdc
OUTPUT VOLTAGE	10% to 90% of Supply Voltage
CENTER REFERENCE	48% to 52% of Supply Voltage
OUTPUT SENSE	The dual outputs can be configured to have positive ramps or a combination of positive and negative ramps
CURRENT CONSUMPTION	< 19mA
CONNECTION	6-way flying lead

### MECHANICAL

BREAKOUT FORCE	3Nm
OPERATING FORCE AT END OF TRAVEL – WITHOUT OVER-PRESS	6.5 $\pm$ 1.5Nm
OPERATING FORCE AT START OF OVER-PRESS	6Nm
OPERATING FORCE TO ENGAGE OVER-PRESS	17Nm
MECHANICAL ANGLE	$\pm$ 25°
START OF OVER-PRESS	$\pm$ 20°
MECHANICAL LIFE	1 million cycles 200,000 cycles with over-press feature
WEIGHT	20g maximum

### ENVIRONMENTAL & LEGISLATIVE

OPERATING TEMPERATURE	-25°C to 80°C	
STORAGE TEMPERATURE	-40°C to 80°C	
ENVIRONMENTAL PROTECTION	The rocker has a design where contamination (liquid or dust) can pass through the mechanism without causing any damage and an IP67 protection of the electronics	
EMC IMMUNITY LEVEL	EN 61000-4-3: 2002	100V/m, 80MHz-1GHz and 1.4-2.7GHz
EMC EMISSIONS LEVEL	EN 61000-6-4: 2011	30MHz-1GHz
ESD IMMUNITY LEVEL	EN 61000-4-2, Level 2: 1995	4kV contact and air discharge
VIBRATION (RANDOM)	EN 60068-2-64: 2008	3.6gn, 10-200Hz, 2h per axis
BUMP	EN 60068-2-27: 2008	25gn, 10ms, 500 bumps in each of 6 directions
FREE-FALL DROP	EN 60068-2-32: 1993	1.0m at level C, 1.2m at level E
SHOCK	EN 60068-2-27: 2008	50g, 6ms, half sine, 3 shocks in each of 6 directions
MTTFd	>700 years	